



DNS® color print is designed especially for colour laser printers, copiers and digital colour presses. Its super smooth surface produces excellent digital print results with sharper, more vibrant colours.



Technical Data: DNS® color print

				160	200	250	300
Grammage	g/m ²	ISO 536		160 ± 6.0	200 ± 6.0	250 ± 7.0	300 ± 8.0
Caliper	mm/1000	ISO 534		176 ± 6	214 ± 7	262 ± 8	315 ± 8
Stiffness L&W	MD mN	ISO 2493		550 ± 50	min 800	min 1200	min 2000
Stiffness L&W	CD mN	ISO 2493		300 ± 40	min 400	min 650	min 1000
Smoothness Bekk	sec	ISO 5627		70 ± 15	60 ± 15	60 ± 15	50 ± 15
Opacity	%	ISO 2471		97.0 ± 1	99.0 ± 1	99.0 ± 1	99.0 ± 1
Brightness with UV	D65 %	ISO 2470		113.5 ± 1.5	113.5 ± 1.5	113.5 ± 1.5	113.5 ± 1.5
CIE Whiteness		ISO 11475		170 ± 3.0	170 ± 3.0	170 ± 3.0	170 ± 3.0

Product meets EN 12281, requirements for copy paper for dry toner imaging processes and ISO 9706, requirements for permanence for paper. Production processes certified according to ISO 9001, ISO 14001 and OHSAS 18001.

SIGNIFICANCE OF VALUES: 2 SIGMA